

Power Busbar Connector

Our power busbar connectors enable high-power densities needed for EVs by providing robust, customizable, pluggable connectors that save space and improve assembly consistency.

PRODUCT
**ENNOVI-
BusMate**

VISIT [ENNOVI.COM](https://www.ennovi.com)
FOR MORE DETAILS

FOLLOW US ON [LINKEDIN](#)

ENNOVI™

COMPACT SIZE



Ultra small footprint conserves PCB space and improves design flexibility for either Press-Fit or SMT applications.

HIGH-POWER DENSITY



Large ampacity-to-size ratio with 40-60 Amp rating (tested at 60-80 Amps).

AUTOMATIC COMPENSATION FOR MISALIGNMENT



Floating Contact Technology accommodates +/- 0.8mm blade offset, +/- 16 degrees of twist, and a range of insertion depths.

APPLICATIONS

High-voltage traction drive motors, low-voltage motion control, servo-steering motors, on-board chargers, transformers, fuses, power junction centers, power converters, inverters and distribution:

+ Electric vehicles

Servo-steering motors, motion control, transformers, fuses, power converters and inverters:

+ Commercial transportation
+ Personal mobility
+ Maritime

Transformers, fuses, junction boxes, power converters and inverters:

+ Charging stations
+ Energy storage
+ Industrial
+ Medical

01. FLOATING CONTACT TECHNOLOGY

+ Accommodates large mating tolerances: offset and angular.

- o +/- 0.8mm mating blade offset and up to +/- 16 degrees of twist.

+ Handles a range of insertion depths.

02. BUSBAR CONNECTION

+ Large ampacity-size ratio: 40 to 60 Amp interfaces up to 60 to 80 Amps.

+ Achieves consistent power coupling by automatically compensating for variations in blade alignment.


+ Separable & pluggable: mates with 0.8mm and 1mm thick Busbars.

03. HIGH PERFORMANCE MATERIALS

+ High temperature construction, rated to 150°C.

04. MOUNT OPTIONS

+ PCB Mount: Press-Fit and Surface Mount (SMT).



DESIGN & MANUFACTURING OPTIONS


+ Customizable and scalable.

+ Configurable for: board-to-blade, board-to-board, and blade-to-blade.


+ Options for tape-and-reel packaging to support highspeed automated placement.

Power Busbar Connector


PRODUCT ENNOVI- BusMate




PRODUCT OFFERING



Press-Fit (9 Lam.)
Part No.: IPX-30013
DC Current: 40 – 60Amps
ROA Temperature: 23°C – 50°C



Surface Mount (9 Lam.)
Part No.: IPX-30035
DC Current: 40 – 60Amps
ROA Temperature: 25°C – 53°C



Surface Mount (14 Lam.)
Part No.: IPX-30055
DC Current: 60 – 80Amps
ROA Temperature:
34°C – 59°C (40Amps at 17°C)

ROA is Rise Over Ambient; Ambient Temperature is 23°C. Test Specifications are listed below.

PF stands for Press-Fit | SMT stands for Surface-Mount Technology. Note: All testing utilize 0.8mm busbar blade. Users must always validate and qualify ENNOVI-BusMate in their own application.

Test Temperature -40°C to 125°C

PERFORMANCE SPECIFICATIONS

VALIDATION TEST	DESCRIPTION	SPECIFICATION	TESTS CRITERIA	TEST RESULTS	CONCLUSION		
Insertion Force	9 Lam. PF			90N +/- 10N	88N		
	9 Lam. SMT	Top Mating Busbar	Average:	90N +/- 10N	Average: 95N	Pass	
	14 Lam. SMT			135N +/- 10N	136N		
4-Wire Contact Resistance	9 Lam. PF				0.104mΩ		
	9 Lam. SMT	SAE/USCAR2-6 5.3.1	Max Resistance:	less than 1.5mΩ	Max:	0.097mΩ	Pass
	14 Lam. SMT						
Current Rating	9 Lam. PF		Constant Current	> 40Amps		> 60Amps	
	9 Lam. SMT	SAE/USCAR2-6 5.3.3	at 55°C ROA:	> 60Amps	Average:	> 58Amps	Pass
	14 Lam. SMT						
Current Cycling	9 Lam. PF					46°C	
	9 Lam. SMT	SAE/USCAR2-6 5.3.4	ROA at rated current:	< 55°C	Max ROA:	46°C	Pass
	14 Lam. SMT						
Mechanical Shock	9 Lam. PF		No discontinuity				
	9 Lam. SMT	SAE/USCAR2-6 5.4.6	(1 microsecond increment)	Visual Inspection	Not Applicable		Pass
	14 Lam. SMT						
Vibration with Thermal Cycling	9 Lam. PF		No discontinuity				
	9 Lam. SMT	SAE/USCAR2-6 5.4.6	(1 microsecond increment)	Visual Inspection	Not Applicable		Pass
	14 Lam. SMT						
Thermal Shock	9 Lam. PF					0.118mΩ	
	9 Lam. SMT	GMW 3191 4.4.2	Max Resistance:	< 1.5mΩ	Max:	0.122mΩ	Pass
	14 Lam. SMT						
Temperature Cycling with Humidity	9 Lam. PF					0.136mΩ	
	9 Lam. SMT	SAE/USCAR2-6 5.6.2	Max Resistance:	< 1.5mΩ	Max:	0.112mΩ	Pass
	14 Lam. SMT						
High Temperature Humidity Exposure	9 Lam. PF					0.118 mΩ	
	9 Lam. SMT	GMW 3191 4.4.4	Max Resistance:	< 1.5mΩ	Max:	0.120mΩ	Pass
	14 Lam. SMT						
High Temperature Exposure - Dry	9 Lam. PF					0.121mΩ	
	9 Lam. SMT	SAE/USCAR2-6 5.6.3	Max Resistance:	< 1.5mΩ	Max:	0.115mΩ	Pass
	14 Lam. SMT						
Mixed Flow Gas	9 Lam. PF					0.141mΩ	
	9 Lam. SMT	VW75174 EN 60512-11-14	Max Resistance:	< 1.5mΩ	Max:	0.122mΩ	Pass
	14 Lam. SMT						